



NERO's range of Parallel Nipples are available threaded BSPP and have variations on length for most sizes

BSP threads are to ISO 228-1  
Made from 316 stainless steel  
Maximum Working Pressure of 50 BAR

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method  
Note 2 Temperatures indicated are those of the Internal fluid  
Note 3 Piping loads, stresses And moments are not taken into account

SIZE	CODE BSP	DIMENSIONS		
		B	A	KG EACH
1/8	PN02	16mm	10.2	0.00
1/8	PN02-30	30mm	10.2	0.01
1/4	PN04	18mm	13.5	0.01
1/4	PN04-30	30mm	13.5	0.01
3/8	PN06	22mm	17.2	0.01
3/8	PN06-40	40mm	17.2	0.02
1/2	PN08	25mm	21.3	0.02
1/2	PN08-50	50mm	21.3	0.03
3/4	PN12	30mm	26.9	0.04
3/4	PN12-60	60mm	26.9	0.04
1	PN16	35mm	33.7	0.05
1	PN16-50	50mm	33.7	0.06
1	PN16-70	70mm	33.7	0.07
1-1/4	PN20	38mm	42.4	0.09
1-1/4	PN20-75	75mm	42.4	0.11
1-1/2	PN24	38mm	48.3	0.12
1-1/2	PN24-75	75mm	48.3	0.13
2	PN32	45mm	60.3	0.14
2	PN32-90	90mm	60.3	0.20
2-1/2	PN40	55mm	76.1	0.24
3	PN48	60mm	88.9	0.37
4	PN64	70mm	114.3	0.51

\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK