



SIZE	CODE BSP	DIMENSIONS			
		A	B	C	KG EACH
1/4 x 1/8	RAFM0402	8	15	16	0.02
3/8 x 1/4	RAFM0604	10.5	15.3	19.3	0.02
1/2 x 1/4	RAFM0804	10.5	18.4	23.8	0.04
1/2 x 3/8	RAFM0806	11	18.4	23.8	0.04
3/4 x 3/8	RAFM1206	11	19.3	29.5	0.05
3/4 x 1/2	RAFM1208	14.5	20	29.5	0.06
1 x 1/2	RAFM1608	14.5	22.6	36.6	0.09
1 x 3/4	RAFM1612	15.5	22.6	36.6	0.09
1-1/4 x 3/4	RAFM2012	15.5	25.4	45.6	0.14
1-1/4 x 1	RAFM2016	18	25.4	45.6	0.14
1-1/2 x 1	RAFM2416	18	25.7	52.2	0.17
1-1/2 x 1-1/4	RAFM2420	20.5	25.7	52.2	0.18
2 x 1-1/4	RAFM3220	20.5	29.6	63.9	0.27
2 x 1-1/2	RAFM3224	20.5	30	63.9	0.27

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Reducing Adaptors are available threaded BSPP. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method
Note 2 Temperatures indicated are those of the Internal fluid
Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.

