





SIZE	PRODUCT CODE	DIMENSIONS		KG EACH
		А	В	NG EACH
1/4 x 1/8	3RS0402N	19	35	0.04
3/8 x 1/4	3RS0604N	25	38	0.06
1/2 x 1/4	3RS0804N	29	48	0.06
1/2 x 3/8	3RS0806N	29	48	0.06
3/4 x 3/8	3RS1206N	35	51	0.19
3/4 x 1/2	3RS1208N	35	51	0.19
1 x 1/2	3RS1608N	45	60	0.39
1 x 3/4	3RS1612N	45	60	0.39
1-1/4 x 3/4	3RS2012N	57	67	0.68
1-1/4 x 1	3RS2016N	57	67	0.68
1-1/2 x 1	3RS2416N	64	79	0.99
1-1/2 x 1-1/4	3RS2420N	64	79	0.99
2 x 1	3RS3216N	76	86	1.80
2 x 1-1/4	3RS3220N	76	86	1.37
2 x 1-1/2	3RS3224N	76	86	1.37

<sup>\*\*</sup> DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Reducing Couplings are available in NPT and Socket Weld configurations - ASME B16.11-2016

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

NPT threads are to ANSI B2.1

Larger sizes are available upon request

Reducing Couplings in BSPP, NPT and Socket Weld can also be supplied as part of our low pressure 150lb range





We also keep Reducing Couplings in Socket Weld 3000# 316/L







SAME DAY DISPATCH ORDERS PLACED BEFORE 4:30PM



