



	$\overline{}$															
PIPE SIZE	DN	CODE BSPP	CODE BSPT	CODE NPT	Α	В	<u> </u>	<u>D</u> '	<u>(E</u> '	<u>ı ғ</u> '	<u> </u>	<u>јн</u> '	<u>, </u>	BOLT	KG EACH	BOLT KIT CODE
1/2	15	F1640.5	F1640.5 BSPT	F1640.5 NPT	45	65	95	35	20	3	14	14	4	4XM12	0.61	BK03
3/4	20	F1640.75	F1640.75 BSPT	F1640.75 NPT	58	75	105	45	24	3	16	14	4	4XM12	0.91	BK03
1	25	F1641.0	F1641.0 BSPT	F1641.0 NPT	68	85	115	52	24	3	16	14	4	4XM12	1.1	BK03
1.25	32	F1641.25	F1641.25 BSPT	F1641.25 NPT	78	100	140	60	26	3	16	18	6	4XM16	1.6	BK04
1.5	40	F1641.5	F1641.5 BSPT	F1641.5 NPT	88	110	150	70	26	3	16	18	6	4XM16	1.78	BK04
2	50	F1642.0	F1642.0 BSPT	F1642.0 NPT	102	125	165	84	28	3	18	18	6	4XM16	2.43	BK04
2.5	65	F1642.5	F1642.5 BSPT	F1642.5 NPT	122	145	185	104	32	3	18	18	6	4XM16	3.18	BK04
2.5	65	F1642.5/8 HOLE	-	- '	122	145	185	104	32	3	18	18	6	8XM16	3.18	BK05
3	80	F1643.0	F1643.0 BSPT	F1643.0 NPT	138	160	200	118	34	3	20	18	8	8XM16	4.12	BK07
4	100	F1644.0	F1644.0 BSPT	F1644.0 NPT	158	180	220	140	40	3	20	18	8	8XM16	4.47	BK07

This flange conforms to EN 1092-1 and is available in 316/L. The threads are to ISO 7/1, 228/1 and ANSI B2.1.

Full material traceablity is available and 3.1B certification can be provided upon request.

Bolt kit sizes shown in the above table are for bolting two flanges together including the thickness of a gasket. If using a wafer pattern valve, longer bolts will be required.

Need a gasket? We keep those too









