



SIZE BSPP (G)	SIZE BSPP (G1)	PRODUCT CODE	PRESSURE (BAR)	A	B	C	D	E A/F	KG EACH
1/8	1/8	EBSN02	350	25.4	25.4	8.1	3.5	4.1	0.03
1/4	1/4	EBSN04	350	25.4	28.6	11.1	5.1	4.2	0.06
3/8	3/8	EBSN06	350	28.5	31.5	12.1	7.2	4.6	0.09
1/2	1/2	EBSN08	315	32.5	31.5	14.1	11.1	6.8	0.15
3/4	3/4	EBSN12	250	41.3	42.5	16.1	15.5	8.7	0.21
1	1	EBSN16	200	44.5	49.5	19.1	19.8	10.1	0.35
1-1/4	1-1/4	EBSN20	160	50.8	54.1	20.1	26.1	10.5	0.55
1-1/2	1-1/2	EBSN24	125	59.1	59.8	22.1	31.7	12.2	0.78
2	2	EBSN32	80	77.5	79.4	25.1	41.3	15.1	1.04

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Swivel 90° Elbows are available in BSPP x BSPP threads, with a 60° internal cone on the Female Swivel and Male thread

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate of Conformity - upon request

BSPP Female & Male threads are to ISO 228/1
60° internal cone to BS 5200

We also keep a Male x Male version of this fitting + Bonded Washers in our Hydraulic range



We stock a wide range of Hydraulic Fittings to suit your requirements

