



SIZE	CODE			DIMENSIONS		
	BSP	NPT	SW	A	B	KG EACH
1/8	T02	T02N	T02SW	13.5	14	0.02
1/4	T04	T04N	T04SW	17	18.5	0.07
3/8	T06	T06N	T06SW	21.4	20.8	0.05
1/2	T08	T08N	T08SW	25.5	25	0.08
3/4	T12	T12N	T12SW	31.3	27.5	0.11
1	T16	T16N	T16SW	38.7	33	0.19
1-1/4	T20	T20N	T20SW	48	40	0.32
1-1/2	T24	T24N	T24SW	53.7	43	0.36
2	T32	T32N	T32SW	66.7	52	0.63
2-1/2	T40	T40N	T40SW	84	61	1.09
3	T48	T48N	T48SW	98	70.5	1.72
4	T64	T64N	T64SW	125	97	3.04

We also keep extended barrel nipples in stock, weld nipples too.



NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK