

### Flexible Tubing Nylon (4-12mm)



Industrial tubing made from flexible nylon. Ideally suited for pneumatic / hydraulic applications such as air brakes, as well as fuel and lube applications.

Also ideal for low toxic or high temperature environments such as breweries or applications involving food contact.

Also ideal for low toxic or high temperature environments such as breweries or applications involving food contact.

#### Key Features:

- Flexible, lightweight and durable over a wide temperature range.
- Smooth inner for improved flow.
- Manufactured from heat and light stabilised Nylon to precise tolerances.
- Available on dispensing drums.
- Boxed available for minimum order quantities.
- Resistant to a wide range of chemicals.
- High resistance to moisture absorption.
- Manufactured in accordance with BS 5409, DIN 73378, DIN 74324 and ISO7628.
- Silicone-free.
- Excellent abrasion resistance.
- 4:1 safety factor.
- RoHS 3 compliant.

#### Sizes:

Available in 30m coils.  
4mm-28mm OD

CODE	EXTERNAL DIA (MM)	INTERNAL DIA (MM)	MAX WORKING PRESSURE (BAR)	MIN BURST PRESSURE (BAR)	WEIGHT PER / MTR	BEND RADIUS
PI-NT4X2.5MMNAT	4	2.5	26	104	0.008	25
PI-NT6X4MMNAT	6	4	24	96	0.017	35
PI-NT8X5.5MMNAT	8	5.5	22	88	0.029	45
PI-NT10X7MMNAT	10	7	22	88	0.039	60
PI-NT12X9MMNAT	12	9	21	84	0.055	70

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

We also stock a range of Push-In fittings to suit our Nylon Tubing



#### Applications:

- Pneumatics
- Air brake, fuel and lube applications
- Production lines (industrial and automotive)



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK