


| SIZE | SCHEDULE 10 | | | | | | SCHEDULE 40 | | | | | |
|-------|--------------|-------------|------------|------|-------|---------|--------------|------------|------------|------|-------|---------|
| | PRODUCT CODE | | DIMENSIONS | | | | PRODUCT CODE | | DIMENSIONS | | | |
| | 316/L | 304/L | A | B | C | KG EACH | 316/L | 304/L | A | B | C | KG EACH |
| 1/2 | BC08/1 | BC08/1-304 | 21.3 | 2.11 | 25.4 | 0.04 | BC08/4 | BC08/4-304 | 21.3 | 2.77 | 25.4 | 0.05 |
| 3/4 | BC12/1 | BC12/1-304 | 26.6 | 2.11 | 25.4 | 0.05 | BC12/4 | BC12/4-304 | 26.6 | 2.87 | 25.4 | 0.06 |
| 1 | BC16/1 | BC16/1-304 | 33.4 | 2.77 | 38.1 | 0.09 | BC16/4 | BC16/4-304 | 33.4 | 3.38 | 38.1 | 0.11 |
| 1-1/4 | BC20/1 | BC20/1-304 | 42.1 | 2.77 | 38.1 | 0.11 | BC20/4 | BC20/4-304 | 42.1 | 3.56 | 38.1 | 0.15 |
| 1-1/2 | BC24/1 | BC24/1-304 | 48.1 | 2.77 | 38.1 | 0.11 | BC24/4 | BC24/4-304 | 48.1 | 3.68 | 38.1 | 0.17 |
| 2 | BC32/1 | BC32/1-304 | 60.3 | 2.77 | 38.1 | 0.13 | BC32/4 | BC32/4-304 | 60.3 | 3.91 | 38.1 | 0.23 |
| 2-1/2 | BC40/1 | BC40/1-304 | 73 | 3.05 | 50.4 | 0.17 | BC40/4 | BC40/4-304 | 73 | 5.16 | 50.4 | 0.42 |
| 3 | BC48/1 | BC48/1-304 | 88.9 | 3.05 | 63.5 | 0.24 | BC48/4 | BC48/4-304 | 88.9 | 5.49 | 63.5 | 0.66 |
| 4 | BC64/1 | BC64/1-304 | 114.3 | 3.05 | 76.2 | 0.36 | BC64/4 | BC64/4-304 | 114.3 | 6.02 | 76.2 | 1.17 |
| 5 | BC80/1 | BC80/1-304 | 141.3 | 3.4 | 88.9 | 0.59 | BC80/4 | BC80/4-304 | 141.3 | 6.55 | 88.9 | 1.90 |
| 6 | BC96/1 | BC96/1-304 | 168.3 | 3.4 | 101.6 | 0.98 | BC96/4 | BC96/4-304 | 168.3 | 7.11 | 101.6 | 2.83 |
| 8 | BC128/1 | BC128/1-304 | 219.08 | 3.76 | 127 | 2.75 | BC128/4 | - | 219.08 | 8.18 | 127 | 5.50 |
| 10 | BC160/1 | BC160/1-304 | 273 | 4.19 | 152.4 | 3.90 | - | - | - | - | - | - |
| 12 | - | BC192/1-304 | 323.8 | 4.47 | 177.8 | 7.05 | - | - | - | - | - | - |

NERO's range of BUTT WELD Caps are made to ANSI B16.9 and MSS SP43. They are available in schedule 10-40 thickness and 316/L or 304/L material grades.

This item is of Far Eastern origin and 3.1b material certificates are available upon request.



Plain bevel



Wall thickness (t)
x* mm to 22 mm

Less than x* = Cut square or slightly chamfer, at manufacturer's option.



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK