





S.NO.	COMPONENT	MATERIAL		
1	HANDLE SLEEVE	PVC		
2	HANDLE	304		
3	GLAND NUT	304		
4	STEM NUT	304		
5	SPRING WASHER	304		
6	STEM PACKING	PTFE		
7	THRUST WASHER	PTFE		
8	JOINT GASKET	PTFE		
9	CAP	CF8/CF8M		
10	BODY	CF8/CF8M		
11	BALL SEAT	RPTFE		
12	BALL	CF8/CF8M		
13	STEM	304/316		



- Pressure rated at 1000 PSI (WOG) 1/4" --> 1"
- Sizes available from $1/4^{\prime\prime}$ up to $1^{\prime\prime}$
- 1-Piece Reduced Port
- Threaded Ends: BSPT (ISO 7.1) BSPP (ISO 228-1)
- Investment casting
- Blow-out proof stem
- Inspection Testing: API 598, / EN12266
- 1/4 turn handle
- PED97/23/EC (CE0035) Approved



SIZE	PRODUCT CODE BSPT / BSPP	ØD	Ød	L	Н	W	S	CV	KG EACH
1/4	MFRBV04	11.6	8	55	31	65	17	3.8	0.04
3/8	MFRBV06	12.5	11.4	55	36	85	21	4	0.11
1/2	MFRBV08	15	13.6	71.5	41	95	25	4.5	0.17
3/4	MFRBV12	20	18.2	78	44	95	32	9	0.25
1	MFRBV16	25	23	91	48	111	38	10	0.40

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **





SAME DAY DISPATCH ORDERS PLACED BEFORE 4:30P



