



SIZE	CODE		DIMENSIONS			
	BSP	LENGTH	A	B	C (BSPP)	KG EACH
1/2	LS08	100MM	21.34	100	52	0.09
3/4	LS12	100MM	26.67	100	54	0.12
1	LS16	150MM	33.4	150	62	0.28
1-1/4	LS20	150MM	42.16	150	70	0.37
1-1/2	LS24	150MM	48.26	150	71	0.43
2	LS32	150MM	60.33	150	82	0.54

\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Long Screw fittings are available threaded BSPP/BSPT

BSPP threads are to ISO 228-1

BSPT threads are to ISO 7-1

Made from 316/L stainless steel

Maximum Working Pressure of 50 BAR

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

