

CODE	ΦD (MM)	G (M5 & BSPP)	A	B	ΦP	H	WEIGHT (G)
PI-4MMCM5	4	M5	5	21.7	9	10	8.5
PI-4MMC2BSPP	4	G1/8	5	19	9	12	10.5
PI-4MMC4BSPP		G1/4	6.5	20.4		17	25
PI-6MMC2BSPP	6	G1/8	5	24.2	11	14	10
PI-6MMC4BSPP		G1/4	6.5	20.7		17	25
PI-6MMC6BSPP		G3/8	6.5	19.7		19	35
PI-6MMC8BSPP		G1/2	9	22.2		24	55.5
PI-8MMC2BSPP	8	G1/8	5	24.7	13.7	14	14.5
PI-8MMC4BSPP		G1/4	6.5	21		17	23.5
PI-8MMC6BSPP		G3/8	6.5	20.2		19	34
PI-8MMC8BSPP		G1/2	9	22.7		24	53.5
PI-10MMC4BSPP	10	G1/4	6.5	27.6	15.5	19	26.5
PI-10MMC6BSPP		G3/8	6.5	22.8		19	28.5
PI-10MMC8BSPP		G1/2	9	23.1		24	50.5
PI-12MMC4BSPP	12	G1/4	6.5	28.9	18.7	19	31
PI-12MMC6BSPP		G3/8	6.5	27.9		19	30
PI-12MMC8BSPP		G1/2	9	25.4		24	43.5

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

### FEATURES

- Fast Connection
- High Temperature up to 150°C
- Small, compact design
- Good resistance to chemical corrosive environments
- Food safety
- Allow full flow through Hose / Tubing

### MATERIAL CONSTRUCTION

- Metal Body - SS 316
- Push Button - SS 316
- Claws - SS301
- Seals - FKM

### SPECIFICATIONS


- Operating Pressure - 0-20 BAR
- Operating Temperature - -20 to 150°C
- Vacuum Rating - To 28" Hg
- Application - Air, Vacuum, Steam Beverage, Oil
- Types - Straight

### FITTINGS ADVANTAGE

- Easy to push in and pull out tubes
- Raw material is SS316L and seal is FKM, for high temp and corrosive environments
- 100% tested, no leakage



SSPC-G



We also stock a range of Push-In fittings to work alongside these fittings



### Applications:

- Pneumatics
- Air brake, fuel and lube applications
- Production lines (industrial and automotive)



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLO AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK