



SIZE	CODE	DIMENSIONS		
	BSP	A	B	KG EACH
1/8	LN02	17.2	7.1	0.01
1/4	LN04	19	7.5	0.0125
3/8	LN06	24	7.7	0.02
1/2	LN08	24.5	8.5	0.0165
3/4	LN12	30	9.8	0.0255
1	LN16	37.5	10.5	0.039
1-1/4	LN20	46.5	11.7	0.063
1-1/2	LN24	53	12.6	0.084
2	LN32	65.5	14.2	0.133
2-1/2	LN40	82	17	0.203
3	LN48	95.5	20	0.307
4	LN64	121.5	22.9	0.5

We also keep extended barrel nipples in stock, weld nipples too.



NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1  
 NPT threads are to ANSI B2.1  
 Made from 316 (CF8M) stainless steel

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method  
 Note 2 Temperatures indicated are those of the Internal fluid  
 Note 3 Piping loads, stresses And moments are not taken into account



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK