



CODE	SIZE (OD) MM	в мм	MAXIMUM WORKING PRESSURE (BAR)	KG / MTR
041316S	4	1	642	0.08
061.5316S	6	1.5	642	0.17
061316S	6	1	428	0.13
062316S	6	2	856	0.20
081.5316S	8	1.5	481	0.24
081316S	8	1	321	0.18
082316S	8	2	642	0.30
101.53165	10	1.5	385	0.32
101316S	10	1	257	0.23
102.03165	10	2	513	0.32
121.53165	12	1.5	321	0.39
121316S	12	1	214	0.28
122.0316S	12	2	428	0.50
141.53165	14	1.5	275	0.47
141316S	14	1	183	0.33
142316S	14	2	367	0.60
151.53168	15	1.5	257	0.51
151316S	15	1	171	0.35
152.0316S	15	2	342	0.65
161.5316S	16	1.5	241	0.55
161316	16	1.5	160	0.38
162.0316S	16	2	321	0.70
162.5316S	16	2.5	401	0.70
181.5316S	18	1.5	214	0.62
182316S	18	2	285	0.80
201.53165	20	1.5	193	0.70
201.3316S 202.0316S	20	2	257	0.70
202.53165	20	2.5	321	1.10
202.53163 203.0316SS	20	3	385	1.10
221.5316S	22	1.5	175	0.77
222.0316S	22	2	233	1.00
223.03165	22	3	321	1.13
251.5316S	25	1.5	154	0.88
251.53165 252.0316S	25	2	205	1.15
	25		257	1.15
252.5316S 253.0316S	25	2.5	308	
281.5316S				1.65
	28 28	1.5 2.5	183 229	1.30
282.53165			+	1.60
282316S	28	2	183	1.30
302316S	30		171	1.40
3033165	30	3	257	2.03
304.0316SS	30	· ·	342	2.60
352316S	35	2	147	1.65
353.0316SS	35	3	220	2.40
383316S	38	3	203	2.63
384316S	38	4	270	3.41
385316S	38	5	338	4.13
423316S	42	3	183	2.93

^{**} DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **



TO WORK OUT THE INSIDE DIAMETER OF PIPE

- Multiply the Wall Thickness by 2
- Then deduct this number off the OD of the Pipe

NERO's range of seamless tube is to ASTM A269/A213 and is available in 316/L material from 4mm to 42mm.

We keep all sizes in full lengths (6 metres) and sell by the metre, this enables us to supply lengths as short as 1 metre long.

We can also offer and accurate cutting service on any of our tube to a tolerance of +/- 1mm.









SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM



