



TO WORK OUT THE INSIDE DIAMETER OF PIPE

- Multiply the Wall Thickness by 2
- Then deduct this number off the OD of the Pipe

NERO's range of Press fit tube is of welded construction and made to TP316L/W.1.4404 / TP316/W1.4401
WRAS approved with certification available
Compatible with any brand of fitting/Tool

SIZE (MM)	PRODUCT CODE	A	B	KG / MTR
15	PF151316W	15MM	1MM	0.351
18	PF181316W	18MM	1MM	0.58
22	PF221.2316W	22MM	1.2MM	0.75
28	PF281.2316W	28MM	1.2MM	0.99
35	PF351.5316W	35MM	1.5MM	1.25
42	PF421.5316W	42MM	1.5MM	1.95
54	PF541.5316W	54MM	1.5MM	2.89
76.1	PF76.1X2.0316W	76.1MM	2MM	3.76
88.9	PF88.9X2.0316W	88.9MM	2MM	4.25
108	PF108X2.0316W	108MM	2MM	5.11

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

Application	Operating temperature	Maximum operating pressure
Hot and cold potable water	0 to 100°C	16 BAR
Heating water	0 to 100°C	16 BAR
Cooling water without antifreeze agent	0 to 100°C	16 BAR
Cooling water with antifreeze agent	-30 to +120°C	16 BAR
Saturated steam	0 to 120°C	2 BAR
Saturated steam	5 to 155°C	5 BAR
Service/Treated water	0 to 100°C	16 BAR
Rainwater/Grey and black water with a pH value of >6.0	0 to 100°C	16 BAR
Extinguishing water	0 to 70°C	16 BAR
Sprinklers	0 to 70°C	16 BAR
Oils, Fuels and Chemicals	Please contact	Please contact

