


- Pressure rated at 1000 PSI (WOG) - 1/4" -> 1"
- Sizes available from 1/4" up to 1"
- Reduced Port
- Threaded Ends: BSPP (ISO 228-1)
- Investment casting
- Blow-out proof stem
- Inspection Testing: API 598, / EN12266
- External Polished
- Max Temperature: -25°C to 180°C

S.NO.	COMPONENT	MATERIAL
1	O-RING	VITON
2	STEM	304/316
3	BOLT	304
4	LEVER	ALUMINIUM ALLOY
5	BODY	CF8/CF8M
6	CAP	CF8/CF8M
7	BALL SEAT (A)	PTFE
8	BALL	304/316
9	BALL SEAT (B)	PTFE
10	THRUST WASHER	PTFE

SIZE	PRODUCT CODE BSPP	D	L	H	W	S	KG EACH
1/4	MINI/MFRBV04	8	39	26.5	22.8	21	0.075
3/8	MINI/MFRBV06	8	41	26.5	22.8	21	0.083
1/2	MINI/MFRBV08	9.2	46	28.3	22.8	24.5	0.12
3/4	MINI/MFRBV12	12.5	55	31.5	22.8	31	0.20
1	MINI/MFRBV16	15	65	34	22.8	38	0.30

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK