



| SIZE | CODE BSP | DIMENSIONS | | |
|-------|-------------|------------|------|---------|
| | | SW | A | KG EACH |
| 1/8 | UFMM02 | 29.1 | 42 | 0.09 |
| 1/4 | UFMM04 | 29.1 | 44.5 | 0.11 |
| 3/8 | UFMM06 | 34 | 48.5 | 0.15 |
| 1/2 | UFMM08 | 37.5 | 68 | 0.16 |
| 3/4 | UFMM12 | 44.5 | 75 | 0.23 |
| 1 | UFMM16 | 53.5 | 87.5 | 0.40 |
| 1-1/4 | UFMM20 | 64 | 93 | 0.54 |
| 1-1/2 | UFMM24 | 71.5 | 103 | 0.72 |
| 2 | UFMM32 | 85.5 | 115 | 1.06 |

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Male x Male PTFE Unions are available threaded BSPT x BSPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
Made from 316 (CF8M) stainless steel

| TABLE 1: PRESSURE-TEMPERATURE RATING | |
|--------------------------------------|---|
| TEMPERATURE (°C) | NO-SHOCK MAXIMUM WORKING PRESSURE (Bar) |
| -20 to 40 | 20 |
| 100 | 16.5 |
| 150 | 15 |
| 200 | 14 |
| 220 | 13.5 |

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method
Note 2 Temperatures indicated are those of the Internal fluid
Note 3 Piping loads, stresses And moments are not taken into account

