



SIZE C (FEMALE)	SIZE T (MALE)	PRODUCT CODE	PRESSURE (BAR)	K	L1	L2	F	F1	KG EACH
1/8	3/8	FBH02	350	9.0	14.0	4.0	19	22	0.027
1/4	1/2	FBH04	350	15.0	21.0	4.0	24	27	0.051
3/8	3/4	FBH06	350	15.0	21.0	5.0	30	32	0.082
1/2	1	FBH08	315	20.0	27.0	6.0	32	36	0.109
3/4	1-1/4	FBH12	250	24.5	34.0	8.0	46	50	0.334
1	1-1/4	FBH16	200	24.50	34.0	8.0	46	50	0.235

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Female Bulkhead fittings are available in BSPP thread form with a 60° internal cone on the male end

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate of Conformity - upon request

BSPP Male & Female threads are to ISO 228/1

Supplied complete with Lock Nut & recessed male thread to accomodate our Bonded Washers to offer superior sealing

**We stock a wide range of Hydraulic Fittings to suit your requirements**



**We also keep a Male version of this fitting + Bonded Washers in our Hydraulic range**

