



GDPRESS fittings offer reliable and consistent performance, combined with an easy installation process using common M-contour design and tooling compatibility

Fluoropolymer (FPM) O-Ring seals are green in colour and are used in our Press Fit as an alternative to the black EPDM version when high temperature applications are being used. They can easily be fitted by removing the EPDM version and pushing these into place

Operating temperature for these Gaskets is -20°C to +200°C

Maximum operating pressure is 16 BAR

All fittings are made from 316L (1.4404)

SIZE	PART No	KG EACH
15	PFGFPM15	0.04
18	PFGFPM18	0.04
22	PFGFPM22	0.09
28	PFGFPM28	0.09
35	PFGFPM35	0.11
42	PFGFPM42	0.40
54	PFGFPM54	0.50
76.1	PFGFPM76.1	2.10
88.9	PFGFPM88.9	3.20
108	PFGFPM108	5.90

EPDM Gaskets are supplied pre-installed in all Press Fit where applicable as standard



**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

Application	Operating temperature	Maximum operating pressure	Seal
Hot and cold potable water	0 to 100°C	16 BAR	EPDM
Heating water	0 to 100°C	16 BAR	EPDM
Cooling water without antifreeze agent	0 to 100°C	16 BAR	EPDM
Cooling water with antifreeze agent	-30 to +120°C	16 BAR	EPDM
Service/Treated water	0 to 100°C	16 BAR	EPDM
Rainwater/Grey and black water with a pH value of >6.0	0 to 100°C	16 BAR	EPDM
Extinguishing water	0 to 70°C	16 BAR	EPDM
Extinguishing water (wet/dry, dry)	0 to 70°C	16 BAR	FPM
Sprinklers	0 to 70°C	16 BAR	EPDM
Oils, Fuels and Chemicals	Please contact	Please contact	FPM

