



SIZE	CODE	A	B	C	D	E	F	KG / 100
1/2	CCDC08	103	39	32.4	32	11	43	12.8
3/4	CCDC12	115	52	32.4	32	12	44	18.0
1	CCDC16	137	61	37.3	39	14	53	30.7
1-1/4	CCDC20	183	81	46.0	48	16	64	54.0
1-1/2	CCDC24	191	89	54.0	49	20	69	66.2
2	CCDC32	201	99	63.7	54	23	77	82.8
2-1/2	CCDC40	213	111	76.4	58	25	83	106.7
3	CCDC48	267	137	92.2	60	28	88	159.2
4	CCDC64	296	166	102.2	63	30	93	222.6
5	CCDC80	322	192	146.0	65	30	95	351.0
6	CCDC96	454	258	176.0	70	33	103	511.0

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

- Available in 316 stainless steel (CF8M)

- BUNA N (Nitrile) seals supplied as standard
 - 100°C maximum temperature (when used with Nitrile seals)
 - Made to standard A-A-59326 (MIL-C-27487) or DIN 2828

- Test Pressures 1/2" - 2" = 17.6 BAR (250 PSI)
 - Test Pressures 2-1/2" = 15.8 BAR (225 PSI)
 - Test Pressures 3" - 4" = 14.8 BAR (200 PSI)
 - Test Pressures 5" - 6" = 10.5 BAR (150 PSI)

We also keep ISO B Quick Release Couplings and Nipples in this range



We also keep other types of Cam fittings to this standard

