



NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

SIZE	CODE BSP	DIMENSIONS		
		B	A	KG EACH
1/8	PN02	16mm	10.2	0.00
1/8	PN02-30	30mm	10.2	0.01
1/4	PN04	18mm	13.5	0.01
1/4	PN04-30	30mm	13.5	0.01
3/8	PN06	22mm	17.2	0.01
3/8	PN06-40	40mm	17.2	0.02
1/2	PN08	25mm	21.3	0.02
1/2	PN08-50	50mm	21.3	0.03
3/4	PN12	30mm	26.9	0.04
3/4	PN12-60	60mm	26.9	0.04
1	PN16	35mm	33.7	0.05
1	PN16-50	50mm	33.7	0.06
1	PN16-70	70mm	33.7	0.07
1-1/4	PN20	38mm	42.4	0.09
1-1/4	PN20-75	75mm	42.4	0.11
1-1/2	PN24	38mm	48.3	0.12
1-1/2	PN24-75	75mm	48.3	0.13
2	PN32	45mm	60.3	0.14
2	PN32-90	90mm	60.3	0.20
2-1/2	PN40	55mm	76.1	0.24
3	PN48	60mm	88.9	0.37
4	PN64	70mm	114.3	0.51



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK