


- Pressure rated at 1000 PSI (WOG) 1/4" --> 2"
- Sizes available from 1/4" up to 2"
- Reduced Port
- Threaded Ends: BSPP (ISO 228-1) NPT (ISO 7.1)
- Investment casting
- Blow-out proof stem
- Inspection Testing: API 598 / EN12266
- Lockable Handle
- PED97/23/EC (CE0035) Approved
- L or T Port options availabe
- 4 sests for rigid ball supporting



S.NO.	COMPONENT MATERIAL			
1	BODY	CF8/CF8M		
2	CAP(1)	CF8/CF8M		
3	CAP(2)	CF8/CF8M		
4	BALL	CF8/CF8M		
5	BALL SEAT	RPTFE		
6	STEM	304/316		
7	THRUST WASHER	PTFE		
8	STEM PACKING	PTFE		
9	GLAND NUT	304		
10	SPRING WASHER	304		
11	NUT	304		
12	HANDLE COVER	PVC		
13	HANDLE COVER	304/316		
14	WASHER	304		
15	THRUST WASHER	304		
15	O-RING	VITON		
17	JOINT GASKET	PTFE		



	PRODUCT	CODE										
SIZE	BSPP	NPT	ØD	W	L	L1	н	В	E	ISO 5211	H1	KG EACH
1/4	RBVT04	RBVT04N	9	139	79	64	73	9	9	F04/03	42	0.74
3/8	RBVT06	RBVT06N	11	139	79	64	73	9	9	F04/03	42	0.78
1/2	RBVT08	RBVT08N	12.5	139	79	64	73	9	9	F04/03	42	0.82
3/4	RBVT12	RBVT12N	16	139	83	68	80	9	9	F04/03	49	1.18
1	RBVT16	RBVT16N	20	160	104	82	95	11	11	F05/04	59.5	1.70
1-1/4	RBVT20	RBVT20N	25	160	111	90	98	11	11	F05/04	63	2.82
1-1/2	RBVT24	RBVT24N	32	185	126	106	110	14	14	F07/05	73.5	3.96
2	RBVT32	RBVT32N	38	185	147	123	119	14	14	F07/05	82.8	6.78

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **





SAME DAY DISPATCH



