



SIZE	CODE BSP	DIMENSIONS		
		B	A	KG EACH
1/8	CTN02	23mm	10.3	0.01
1/4	CTN04	24mm	13.7	0.02
3/8	CTN06	25mm	17.2	0.02
1/2	CTN08	29mm	21.3	0.04
3/4	CTN12	32mm	26.7	0.05
1	CTN16	38mm	33.4	0.09
1-1/4	CTN20	38mm	42.2	0.12
1-1/2	CTN24	44mm	48.3	0.16
2	CTN32	44mm	60.3	0.23
2-1/2	CTN40	57mm	76.1	0.38
3	CTN48	64mm	88.9	0.54
4	CTN64	76mm	114.3	0.93

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Close Taper Nipples are available threaded BSPT

BSPT threads are to ISO 7-1

Made from 316 stainless steel

Maximum Working Pressure of 50 BAR

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLO AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK