



SIZE	PRODUCT CODE BSPT	PRODUCT CODE NPT	DIMENSIONS			KG EACH
			A	B	C	
1/4 x 1/8	3RB0402T	3RB0402N	13	3	16	0.02
3/8 x 1/8	3RB0602T	3RB0602N	13	4	18	0.03
3/8 x 1/4	3RB0604T	3RB0604N	13	4	18	0.02
1/2 x 1/8	3RB0802T	3RB0802N	16	5	22	0.04
1/2 x 1/4	3RB0804T	3RB0804N	16	5	22	0.04
1/2 x 3/8	3RB0806T	3RB0806N	16	5	22	0.03
3/4 x 1/4	3RB1204T	3RB1204N	18	6	28	0.07
3/4 x 3/8	3RB1206T	3RB1206N	18	6	28	0.07
3/4 x 1/2	3RB1208T	3RB1208N	18	6	28	0.06
1 x 1/4	3RB1604T	3RB1604N	21	6	35	0.14
1 x 3/8	3RB1606T	3RB1606N	21	6	35	0.14
1 x 1/2	3RB1608T	3RB1608N	21	6	35	0.14
1 x 3/4	3RB1612T	3RB1612N	21	6	35	0.10
1-1/4 x 1/2	3RB2008T	3RB2008N	22	7	47	0.20
1-1/4 x 3/4	3RB2012T	3RB2012N	22	7	47	0.20
1-1/4 x 1	3RB2016T	3RB2016N	22	7	47	0.18
1-1/2 x 3/4	3RB2412T	3RB2412N	22	8	52	0.30
1-1/2 x 1	3RB2416T	3RB2416N	22	8	52	0.29
1-1/2 x 1-1/4	3RB2420T	3RB2420N	22	8	52	0.26
2 x 1	3RB3216T	3RB3216N	24	9	64	0.45
2 x 1-1/4	3RB3220T	3RB3220N	24	9	64	0.42
2 x 1-1/2	3RB3224T	3RB3224N	24	9	64	0.39

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Reducing Bushes are available in BSPT, NPT and split thread configurations i.e. NPT/BSPP, NPT/BSPT and BSPT/NPT - ASME B16.11-2016

Pressure rating up to 400 BAR (6000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

BSPT threads are to ISO 7.1  
NPT threads are to ANSI B2.1

Larger sizes are available upon request

Reducing Bushes and Nipples can also be supplied as part of our low pressure 150lb range



We also keep Hexagon Reducing Bushes in BSPP as part of our Hydraulic Range

