


## BSPP CONE SEAT MALE x MALE 90° ELBOW 316





| SIZE<br>BSPP (G) | PRODUCT<br>CODE | PRESSURE<br>(BAR) | А    | В    | С    | D    | KG EACH |
|------------------|-----------------|-------------------|------|------|------|------|---------|
| 1/8              | EBM02           | 350               | 25.4 | 25.4 | 8.1  | 3.5  | 0.03    |
| 1/4              | EBM04           | 350               | 25.4 | 25.4 | 11.1 | 5.1  | 0.06    |
| 3/8              | EBM06           | 350               | 28.5 | 28.5 | 12.1 | 8.1  | 0.09    |
| 1/2              | EBM08           | 315               | 32.5 | 32.5 | 14.1 | 11.1 | 0.15    |
| 3/4              | EBM12           | 250               | 41.3 | 41.3 | 16.1 | 16.6 | 0.21    |
| 1                | EBM16           | 200               | 44.5 | 44.5 | 19.1 | 22.2 | 0.35    |
| 1-1/4            | EBM20           | 160               | 50.8 | 50.8 | 20.1 | 28.6 | 0.55    |
| 1-1/2            | EBM24           | 125               | 59.1 | 59.1 | 22.1 | 33.3 | 0.78    |
| 2                | EBM32           | 80                | 77.5 | 77.5 | 25.1 | 46.1 | 1.04    |

\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Hydraulic 90° Elbows are available in BSPP x BSPP threads, with a 60° internal cone on both ends of the Male x Male threads

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate if Conformity - upon request

BSPP Male threads are to ISO 228/1 60° internal cone to BS 5200

We stock a wide range of Hydraulic Fittings to suit your requirements



We also keep a Swivel Female x Male version of this fitting + Bonded Washers in our Hydraulic range







SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM



