



SIZE	CODE		DIMENSIONS		
	BSP	NPT	B	A	KG EACH
1/8	WN02	WN02N	30mm	10.3	0.01
1/4	WN04	WN04N	30mm	13.7	0.02
3/8	WN06	WN06N	30mm	17.2	0.03
1/2	WN08	WN08N	35mm	21.3	0.04
3/4	WN12	WN12N	40mm	26.7	0.07
1	WN16	WN16N	40mm	33.4	0.10
1-1/4	WN20	WN20N	50mm	42.2	0.16
1-1/2	WN24	WN24N	50mm	48.3	0.18
2	WN32	WN32N	50mm	60.3	0.26
2-1/2	WN40	WN40N	60mm	76.1	0.40
3	WN48	WN48N	70mm	88.9	0.59
4	WN64	WN64N	80mm	114.3	0.97
5	WN80	-	100mm	141.3	1.50
6	WN96	-	100mm	168.3	2.25

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Weld Nipples are available threaded BSPT and NPT

BSP threads are to ISO 7-1  
NPT threads are to ANSI B2.1  
Made from 316/L stainless steel pipe  
Maximum Working Pressure of 50 BAR

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method  
Note 2 Temperatures indicated are those of the Internal fluid  
Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.