



SIZE	CODE BSP	DIMENSIONS		
		A	B	KG EACH
1/8	LN02	17.2	7.1	0.01
1/4	LN04	19	7.5	0.01
3/8	LN06	24	7.7	0.02
1/2	LN08	24.5	8.5	0.02
3/4	LN12	30	9.8	0.03
1	LN16	37.5	10.5	0.04
1-1/4	LN20	46.5	11.7	0.06
1-1/2	LN24	53	12.6	0.08
2	LN32	65.5	14.2	0.13
2-1/2	LN40	82	17	0.20
3	LN48	95.5	20	0.31
4	LN64	121.5	22.9	0.50

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of 150Lb Lock Nuts are available threaded BSPP. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLO AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK