



SIZE	CODE		DIMENSIONS		
	BSP	NPT	B	A	KG EACH
1/8	WN02	WN02N	30mm	10.3	0.01
1/4	WN04	WN04N	30mm	13.7	0.02
3/8	WN06	WN06N	30mm	17.2	0.03
1/2	WN08	WN08N	35mm	21.3	0.04
3/4	WN12	WN12N	40mm	26.7	0.07
1	WN16	WN16N	40mm	33.4	0.10
1-1/4	WN20	WN20N	50mm	42.2	0.16
1-1/2	WN24	WN24N	50mm	48.3	0.18
2	WN32	WN32N	50mm	60.3	0.26
2-1/2	WN40	WN40N	60mm	76.1	0.40
3	WN48	WN48N	70mm	88.9	0.59
4	WN64	WN64N	80mm	114.3	0.97
5	WN80	-	100mm	141.3	1.50
6	WN96	-	100mm	168.3	2.25

NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK