



A MM	CODE	в мм	MAXIMUM WORKING	Kg/pmtr
			PRESSURE BAR	
4	041316S	1	642	0.075
6	061.5316S	1.5	642	0.169
6	061316S	1	428	0.125
6	062316S	2	856	0.2
8	081.5316S	1.5	481	0.244
8	081316S	1	321	0.175
8	082316S	2	642	0.3
10	101.5316S	1.5	385	0.319
10	101316S	1	257	0.225
10	102.0316S	2	513	0.319
12	121.5316S	1.5	321	0.394
12	121316S	1	214	0.275
12	122.0316S	2	428	0.501
14	141.5316S	1.5	275	0.47
14	141316S	1	183	0.326
14	142316S	2	367	0.601
15	151.5316S	1.5	257	0.507
15	151316S	1	171	0.351
15	152.0316S	2	342	0.651
16	161.5316S	1.5	241	0.545
16	161316	1	160	0.376
16	162.0316S	2	321	0.701
16	162.5316S	2.5	401	0.845
18	181.5316S	1.5	214	0.62
18	182316S	2	285	0.801
20	201.5316S	1.5	193	0.695
20	202.0316S	2	257	0.901
20	202.5316S	2.5	321	1.096
20	203.0316SS	3	385	1.277
22	221.5316S	1.5	175	0.77
22	222.0316S	2	233	1.002
25	251.5316S	1.5	154	0.883
25	252.0316S	2	205	1.152
25	252.5316S	2.5	257	1.409
25	253.0316S	3	308	1.653
28	281.5316S	1.5	183	1.302
28	282.5316S	2.5	229	1.596
28	282316S	2	183	1.302
30	302316S	2	171	1.402
30	303316S	3	257	2.028
30	304.0316SS	4	342	2.604
35	352316S	2	147	1.653
35	353.0316SS	3	220	2.404
38	383316S	3	203	2.629
38	384316S	4	270	3.405
38	385316S	5	338	4.132
42	423316S	3	183	2.93



NERO's range of seamless tube is to ASTM A269/A213 and is available in 316/L material from 4mm to 42mm.

We keep all sizes in full random lengths (6 metres) and sell by the metre, this enables us to supply lengths as short as 1 metre long.

We can also offer and accurate cutting service on any of our tube to a tolerance of +/- 1mm.











