



GDPRESS fittings offer reliable and consistent performance, combined with an easy installation process using common M-countour design and tooling compatability.

Each end has a toroidal seat, holding a rubber LBP (Leak before press) O-ring gasket. The fittings are installed with blue sleeves, which easily peel off after the pressing process.

All fittings are made from 316L (1.4404)
WRAS approved

Optional Fluoropolymer (FPM) O-rings are also available which offer higher heat and chemical resistance



SIZE	PART No	D	L	WEIGHT KG EACH
15	PFCAP15	15	33.5	0.023
18	PFCAP18	18	34.5	0.028
22	PFCAP22	22	39.2	0.04
28	PFCAP28	28	47.5	0.06
35	PFCAP35	35	51	0.079
42	PFCAP42	42	59	0.115
54	PFCAP54	54	67	0.163
76.1	PFCAP76.1	76.1	94	0.422
88.9	PFCAP88.9	88.9	103	0.543
108	PFCAP108	108	124	0.787

Application	Operating temperature	Maximum operating pressure	Seal
Hot and cold potable water	0 to 100°C	16 BAR	EPDM
Heating water	0 to 100°C	16 BAR	EPDM
Cooling water without antifreeze agent	0 to 100°C	16 BAR	EPDM
Cooling water with antifreeze agent	-30 to +120°C	16 BAR	EPDM
Service/Treated water	0 to 100°C	16 BAR	EPDM
Rainwater/Grey and black water with a pH value of >6.0	0 to 100°C	16 BAR	EPDM
Extinguishing water	0 to 70°C	16 BAR	EPDM
Extinguishing water (wet/dry, dry)	0 to 70°C	16 BAR	FPM
Sprinklers	0 to 70°C	16 BAR	EPDM
Oils, Fuels and Chemicals	Please contact	Please contact	FPM



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK