



SIZE	CODE		DIMENSIONS		
	BSP	NPT	A	B	KG EACH
1/8	HC02	HC02N	12.5	11.8	0.01
1/4	HC04	HC04N	16	15	0.02
3/8	HC06	HC06N	19.5	15.4	0.02
1/2	HC08	HC08N	24	17.1	0.04
3/4	HC12	HC12N	29.5	18.5	0.06
1	HC16	HC16N	36.5	21	0.09
1-1/4	HC20	HC20N	45.5	23.7	0.15
1-1/2	HC24	HC24N	52	23.7	0.17
2	HC32	HC32N	64	27.5	0.27
2-1/2	HC40	HC40N	81	31.7	0.48
3	HC48	HC48N	94.5	35.1	0.72
4	HC64	HC64N	120.5	41.6	1.23

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Hex Caps are available threaded BSPP and NPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

Looking for a plug? we keep those too.

