



| SIZE    | PRODUCT CODE | B    | C    |      | D    | A    | G (MIN) | J (MIN) | KG EACH |
|---------|--------------|------|------|------|------|------|---------|---------|---------|
|         |              |      | AVG  | MIN  |      |      |         |         |         |
| 1 x 1/2 | 3RT1608SW    | 33.9 | 5.69 | 4.98 | 26.7 | 22.5 | 4.55    | 12.5    | 0.70    |
|         |              | 21.8 | 4.67 | 4.09 | 15.8 | 15.5 | 3.73    | 3.73    |         |

| SIZE    | PRODUCT CODE | B    | C    |      | D    | A    | G (MIN) | J (MIN) | KG EACH |
|---------|--------------|------|------|------|------|------|---------|---------|---------|
|         |              |      | AVG  | MIN  |      |      |         |         |         |
| 1 x 3/4 | 3RT1612SW    | 33.9 | 5.69 | 4.98 | 26.7 | 22.5 | 4.55    | 12.5    | 0.75    |
|         |              | 27.2 | 4.90 | 4.27 | 21.0 | 19.0 | 3.91    | 12.5    |         |

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Reducing Tee's are available in Socket Weld

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

Socket Weld ends are to ASME B16.11-2016 / BS3799

Larger sizes are available upon request

Equal and Reducing Tee's can also be supplied as part of our low pressure 150lb

**We also keep Equal Tee's in Socket Weld 3000lb 316/L**

