



SIZE	CODE	DIMENSIONS				
	BW	A	H	D	S	KG EACH
1/8	UCBW02	40	14	10.29	29	0.075
1/4	UCBW04	38	13.5	13.72	29	0.071
3/8	UCBW06	38.5	14.5	17.15	34	0.083
1/2	UCBW08	40	14.5	21.34	37.5	0.107
3/4	UCBW12	41	14	26.67	44.5	0.142
1	UCBW16	47	17	33.4	53.5	0.236
1-1/4	UCBW20	48.5	17	42.16	64	0.337
1-1/2	UCBW24	51	18	48.26	71.5	0.437
2	UCBW32	56.5	21	60.33	85.5	0.649

Not the union you are looking for? see below for more options

NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK