



| SIZE | PRODUCT CODE BSPT | PRODUCT CODE NPT | LENGTH OF THREAD (MIN) | | A | G (MIN) | H | KG EACH |
|-------|----------------------|---------------------|------------------------|------|----|---------|----|---------|
| | | | B | L2 | | | | |
| 1/4 | 3E04T | 3E04N | 8.1 | 10.2 | 25 | 3.30 | 25 | 0.15 |
| 3/8 | 3E06T | 3E06N | 9.1 | 10.4 | 28 | 3.51 | 33 | 0.29 |
| 1/2 | 3E08T | 3E08N | 10.9 | 13.6 | 33 | 4.09 | 38 | 0.42 |
| 3/4 | 3E12T | 3E12N | 12.7 | 13.9 | 38 | 4.32 | 46 | 0.62 |
| 1 | 3E16T | 3E16N | 14.7 | 17.3 | 44 | 4.98 | 56 | 1.14 |
| 1-1/4 | 3E20T | 3E20N | 17.0 | 18.0 | 51 | 5.28 | 62 | 1.42 |
| 1-1/2 | 3E24T | 3E24N | 17.8 | 18.4 | 60 | 5.56 | 75 | 2.63 |
| 2 | 3E32T | 3E32N | 19.0 | 19.2 | 64 | 7.14 | 84 | 2.92 |

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of 90 Degree Elbows are available in BSPT, NPT and Socket Weld configurations - ASME B16.11-2016

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

BSPT threads are to ISO 7.1
NPT threads are to ANSI B2.1

Larger sizes are available upon request

Elbows can also be supplied as 90 or 45 Degree as part of our low pressure 150lb



We also keep 90 Degree Elbows in Socket Weld 3000lb 316/L

