





SIZE BSPP (G)	SIZE BSPT (R)	PRODUCT CODE	PRESSURE (BAR)	А	В	С	D	E	F	HEX 1	HEX 2	KG EACH
1/8	1/8	FST02	350	30.5	13.1	10.1	3.5	4.1	5.5	12.7	14.3	0.03
1/4	1/4	FST04	350	37.2	15.1	13.1	5.1	4.2	7.1	15.9	18.1	0.05
3/8	3/8	FST06	350	43.6	16.5	14.1	7.1	4.6	10.3	18.1	22.2	0.09
1/2	1/2	FST08	315	47.2	16.5	17.1	11.1	6.8	13.9	22.2	25.6	0.15
3/4	3/4	FST12	250	55.3	17.5	18.1	15.5	8.7	19.1	28.6	31.7	0.21
1	1	FST16	200	63.3	21.2	22.2	19.8	10.1	23.8	34.9	38.1	0.35
1-1/4	1-1/4	FST20	160	68.3	21.5	22.2	26.1	10.5	32.5	41.3	47.2	0.55
1-1/2	1-1/2	FST24	125	80.5	26.4	24.1	31.7	12.2	38.1	50.8	56.4	0.78
2	2	FST32	80	90.1	30.1	27.1	41.3	15.1	46.1	63.5	69.8	1.04

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Swivel Adaptors are available in BSPP x BSPT threads, with a 60° internal cone on the Female Swivel end and BSPT the other in a Male thread

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate if Conformity - upon request

BSPP Female thread are to ISO 228/1 BSPT Male thread are to ISO 7-1 60° internal cone to BS 5200

We stock a wide range of Hydraulic Fittings to suit your requirements



We also keep a BSPP Male version of this fitting + Bonded Washers in our Hydraulic range







SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM



