



GDPRESS fittings offer reliable and consistent performance, combined with an easy installation process using common M-contour design and tooling compatibility.

Each end has a toroidal seat, holding a rubber LBP (Leak before press) O-ring gasket. The fittings are installed with blue sleeves, which easily peel off after the pressing process.

All fittings are made from 316L (1.4404)
WRAS approved

Optional Fluoropolymer (FPM) O-rings are also available which offer higher heat and chemical resistance



SIZE	PART No	D-R-D	L	L1	LZ	Z1	KG EACH
15x1/2"x15	PFMT15X1/2BSPT	15-Rp1/2-15	66	33	38	13	0.07
18x1/2"x18	PFMT18X1/2BSPT	18-Rp1/2-18	68	34	39	14	0.09
22x1/2"x22	PFMT22X1/2BSPT	22-Rp1/2-22	74	37	41	16	0.10
22x3/4"x22	PFMT22X3/4BSPT	22-Rp3/4-22	74	37	45	16	0.14
22x1"x22	PFMT22X1BSPT	22-Rp1-22	74	37	48	16	0.16
28x1/2"x28	PFMT28X1/2BSPT	28-Rp1/2-28	84	42	44	19	0.13
28x1"x28	PFMT28X1BSPT	28-Rp1-28	84	42	51	19	0.19
35x3/4"x35	PFMT35X3/4BSPT	35-R3/4-35	100	50	51	35	0.20
35x11/4"x35	PFMT35X11/4BSPT	35-Rp11/4-35	100	50	56	24	0.26

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

Application	Operating temperature	Maximum operating pressure	Seal
Hot and cold potable water	0 to 100°C	16 BAR	EPDM
Heating water	0 to 100°C	16 BAR	EPDM
Cooling water without antifreeze agent	0 to 100°C	16 BAR	EPDM
Cooling water with antifreeze agent	-30 to +120°C	16 BAR	EPDM
Service/Treated water	0 to 100°C	16 BAR	EPDM
Rainwater/Grey and black water with a pH value of >6.0	0 to 100°C	16 BAR	EPDM
Extinguishing water	0 to 70°C	16 BAR	EPDM
Extinguishing water (wet/dry, dry)	0 to 70°C	16 BAR	FPM
Sprinklers	0 to 70°C	16 BAR	EPDM
Oils, Fuels and Chemicals	Please contact	Please contact	FPM



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLo AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK