


### REDUCING ADAPTOR



SIZE	PART No	D	D1	H	Z	WEIGHT
						KG EACH
18x15	PFRA1815	18	15	60	40	0.039
22x15	PFRA2215	22	15	63	43	0.043
22x18	PFRA2218	22	18	62	42	0.045
28x15	PFRA2815	28	15	66	46	0.056
28x18	PFRA2818	28	18	64	44	0.059
28x22	PFRA2822	28	22	62	41	0.061
35x15	PFRA3515	35	15	72	51	0.078
35x18	PFRA3518	35	18	77	57	0.082
35x22	PFRA3522	35	22	71	50	0.084
35x28	PFRA3528	35	28	78	55	0.085
42x15	PFRA4215	42	15	82	61	0.106
42x18	PFRA4218	42	18	82	62	0.111
42x22	PFRA4222	42	22	94	73	0.126
42x28	PFRA4228	42	28	83	60	0.119
42x35	PFRA4235	42	35	77	51	0.115
54x15	PFRA5415	54	15	95	74	0.168
54x18	PFRA5418	54	18	94	73	0.174
54x22	PFRA5422	54	22	95	74	0.165
54x28	PFRA5428	54	28	100	77	0.192
54x35	PFRA5435	54	35	99	73	0.187
54x42	PFRA5442	54	42	92	62	0.175
76.1x54	PFRA76.1X54	76.1	54	146	111	0.465
88.9x54	PFRA88.9X54	88.9	54	163	128	0.591
88.9x76.1	PFRA88.9X76.1	88.9	76.1	161	108	0.676
108x54	PFRA108X54	108	54	163	128	0.739
108x76.1	PFRA108X76.1	108	76.1	184	131	0.859
108x88.9	PFRA108X88.9	108	88.9	203	143	1.045

\*316L/1.4404 SS

\*-35°C to +135°C (EPDM Seal)

\*-20°C to +200°C (Optional FPM Seal)

\*Maximum 16 BAR Operating pressure

\*WRAS/DVGW Approved

\*Sizes 15MM to 108MM

\*Female threads Parallel Rp to EN10226-1/ISO7-1

\*Male threads Taper Rc to EN10226-1/ISO7-1

\*\*DIMENSIONS SUBJECT TO CHANGE, PLEASE CONTACT US IF CRITICAL\*\*