



SIZE	CODE BSP	THREAD	DIMENSIONS				
			B	A	L	SW	KG EACH
1/4	FHT04	1/4	6.3	3	42.5	19	0.03
5/16	FHT05	1/4	8	5	42.5	19	0.04
3/8	FHT06	3/8	9.53	6.5	47	21.4	0.06
1/2	FHT08	1/2	12.7	7.8	61.7	26.7	0.06
3/4	FHT12	3/4	19.05	15	58	31.6	0.10
1	FHT16	1	25.4	19.3	66.5	37.8	0.21
1-1/4	FHT20	1-1/4	31.8	26.8	69.2	47.5	0.25
1-1/2	FHT24	1-1/2	38.1	32.5	87.1	55	0.31
2	FHT32	2	50.8	43.3	90.5	66	0.61

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Female Hosetails are available threaded BSPP. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1  
Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLA AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK