



SIZE	CODE BSP	DIMENSIONS			
		A	B	Z	KG EACH
1/8	Y02	14	17	8.5	0.10
1/4	Y04	17.4	20	10	0.11
3/8	Y06	21.5	23	11.5	0.11
1/2	Y08	26.5	27	13.5	0.12
3/4	Y12	33	32	16	0.17
1	Y16	40.5	38	19	0.30
1-1/4	Y20	50	45	22.5	0.43
1-1/2	Y24	57	48	24	0.57
2	Y32	70.5	57	28.5	1.05

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Y-Pieces are available threaded BSPP. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1  
Made from 316 (CF8M) stainless steel

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method  
 Note 2 Temperatures indicated are those of the Internal fluid  
 Note 3 Piping loads, stresses And moments are not taken into account

