



SIZE	CODE BSP	DIMENSIONS		
		A	B	KG EACH
1/8	LN02/DIN431	17.2	7	0.01
1/4	LN04/DIN431	22	6	0.01
3/8	LN06/DIN431	27	7	0.02
1/2	LN08/DIN431	32	8	0.02
3/4	LN12/DIN431	36	9	0.03
1	LN16/DIN431	46	10	0.04
1-1/4	LN20/DIN431	55	11	0.06
1-1/2	LN24/DIN431	60	12	0.08
2	LN32/DIN431	75	13	0.13
2-1/2	LN40/DIN431	95	16	0.20
3	LN48/DIN431	105	19	0.31
4	LN64/DIN431	131	22	0.50

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of DIN Lock Nuts are available threaded BSPP. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
 NPT threads are to ANSI B2.1
 Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK