



SIZE BSPB (G)	PRODUCT CODE	PRESSURE (BAR)	A	B	C	D	HEX	KG EACH
1/8	EFT02	350	25.4	25.4	3.5	4.1	14.3	0.03
1/4	EFT04	350	25.4	25.4	4.7	4.2	18.1	0.06
3/8	EFT06	350	31.7	31.7	8.1	4.6	22.2	0.09
1/2	EFT08	315	36.1	36.1	11.1	6.8	25.6	0.15
3/4	EFT12	250	42.5	42.5	16.6	8.7	31.7	0.21
1	EFT16	200	48.8	48.8	22.2	10.1	38.1	0.35
1-1/4	EFT20	160	54.1	54.1	28.5	10.5	47.2	0.55
1-1/2	EFT24	125	59.3	59.3	33.3	12.2	56.4	0.78
2	EFT32	80	79.4	79.4	46.1	15.1	69.8	1.04

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Hydraulic Swivel Tee's are available in Female BSPB threads, with a 60° internal cone on all outlets of the Male threads

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate of Conformity - upon request

BSPB Female threads are to ISO 228/1  
60° internal cone to BS 5200

We stock a wide range of Hydraulic Fittings to suit your requirements



We also keep a Male version of this fitting + Bonded Washers in our Hydraulic range

