



GDPRESS fittings offer reliable and consistent performance, combined with an easy installation process using common M-contour design and tooling compatibility

Hydrogenated Nitrile Butadiene Rubber (HNBR) O-Ring seals are yellow in colour and are used in our Press Fit as an alternative to the black EPDM version when Gas applications are being used. They can easily be fitted by removing the EPDM version and pushing these into place

Operating temperature for these Gaskets is -20°C to +70°C

Maximum operating temperature is 5 BAR

WRAS approved

EPDM Gaskets are supplied pre-installed in all Press Fit where applicable as standard



| SIZE | PART No | KG EACH |
|------|-------------|---------|
| 15 | PFGHNBR15 | 0.04 |
| 18 | PFGHNBR18 | 0.04 |
| 22 | PFGHNBR22 | 0.09 |
| 28 | PFGHNBR28 | 0.09 |
| 35 | PFGHNBR35 | 0.11 |
| 42 | PFGHNBR42 | 0.40 |
| 54 | PFGHNBR54 | 0.50 |
| 76.1 | PFGHNBR76.1 | 2.10 |
| 88.9 | PFGHNBR88.9 | 3.20 |
| 108 | PFGHNBR108 | 5.90 |

| | | | CrNiMo steel 1.4401 / 316 |
|---------------------|--------------|---|---------------------------|
| For natural gases | -20 – +70 °C | MOP 5/malleable cast iron 5 ²⁾ | ✓ |
| For liquefied gases | -20 – +70 °C | MOP 5/malleable cast iron 5 ²⁾ | ✓ |

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

