





SIZE	PRODUCT CODE	PRODUCT CODE	DIMENSIONS		KG EACH
	SW / BSPT	SW / NPT	D	L	NG EACH
1/4	3S04SW/BSPT	3S04SW/NPT	19	35	0.05
3/8	3S06SW/BSPT	3S06SW/NPT	22	38	0.07
1/2	3S08SW/BSPT	3S08SW/NPT	28	48	0.14
3/4	3S12SW/BSPT	3S12SW/NPT	35	51	0.23
1	3S16SW/BSPT	3S16SW/NPT	44	60	0.45
1-1/4	3S20SW/BSPT	3S20SW/NPT	57	67	0.73
1-1/2	3S24SW/BSPT	3S24SW/NPT	64	79	1.18
2	3S32SW/BSPT	3S32SW/NPT	76	86	1.40

NERO's range of Full Couplings are available in BSPT, BSPP, NPT and Socket Weld configurations with this version having Socket Weld one side and either BSPT or NPT thread the other side

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

Socket Weld ends are to ASME B16.11-2016 / BS3799 BSPT threads are to ISO 7.1 NPT threads are to ANSI B2.1

Larger sizes are available upon request

Couplings can also be supplied as part of our low pressure 150lb range





We also keep Full Couplings in BSPT, BSPP, NPT and Socket Weld in 3000lb 316/L







SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM



