





SIZE BSPP (G)	PRODUCT CODE	PRESSURE (BAR)	А	В	С	HEX	KG EACH
1/8	EBF02	350	25.4	3.5	4.1	14.3	0.03
1/4	EBF04	350	28.6	4.7	4.2	18.1	0.06
3/8	EBF06	350	31.5	8.1	4.6	22.2	0.09
1/2	EBF08	315	31.5	11.1	6.8	25.6	0.15
3/4	EBF12	250	42.5	16.6	8.7	31.7	0.21
1	EBF16	200	49.5	22.2	10.1	38.1	0.35
1-1/4	EBF20	160	54.1	28.5	10.5	47.2	0.55
1-1/2	EBF24	125	59.8	33.3	12.2	56.4	0.78
2	EBF32	80	79.4	46.1	15.1	69.8	1.04

<sup>\*\*</sup> DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Swivel 90° Elbows are available with BSPP threads, with a 60° internal cone on the Female Swivel ends.

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate if Conformity - upon request

BSPP Female threads are to ISO 228/1 60° internal cone to BS 5200

We stock a wide range of Hydraulic Fittings to suit your requirements



We also keep a Male x Male version of this fitting + Bonded Washers in our Hydraulic range







SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM



