



REDUCING SIZE

SIZE	PRODUCT CODE BSPT	PRODUCT CODE NPT	DIMENSIONS						KG EACH
			A (MIN)	W (MIN)	E (MIN)	b	C (MIN)	F (MIN)	
1/4 x 1/8	3RN0402T	3RN0402N	15	31	15	5	6	10	0.04
3/8 x 1/8	-	3RN0602N	18	34	16	5	8	10	0.05
3/8 x 1/4	3RN0604T	3RN0604N	18	39	16	8	8	15	0.05
1/2 x 1/8	-	3RN0802N	22	38	20	8	8	10	0.08
1/2 x 1/4	3RN0804T	3RN0804N	22	43	20	8	8	15	0.09
1/2 x 3/8	3RN0806T	3RN0806N	22	44	20	11	8	16	0.09
3/4 x 1/4	-	3RN1204N	27	45	21	11	9	15	0.15
3/4 x 3/8	3RN1206T	3RN1206N	27	46	21	11	9	16	0.15
3/4 x 1/2	3RN1208T	3RN1208N	27	50	21	14	9	20	0.15
1 x 3/8	-	3RN1606N	35	50	25	11	9	16	0.27
1 x 1/2	3RN1608T	3RN1608N	35	55	25	14	10	20	0.27
1 x 3/4	3RN1612T	3RN1612N	35	56	25	19	10	21	0.27
1-1/4 x 1/2	-	3RN2008N	47	55	21	14	14	20	0.45
1-1/4 x 3/4	3RN2012T	3RN2012N	47	56	21	19	14	21	0.45
1-1/4 x 1	3RN2016T	3RN2016N	47	63	24	24	14	25	0.45
1-1/2 x 3/4	-	3RN2412N	50	63	26	19	16	21	0.62
1-1/2 x 1	3RN2416T	3RN2416N	50	67	26	24	16	25	0.62
1-1/2 x 1-1/4	3RN2420T	3RN2420N	50	64	26	32	16	22	0.62
2 x 1	3RN3216T	3RN3216N	62	70	27	24	18	25	1.03
2 x 1-1/4	3RN3220T	3RN3220N	62	67	27	32	18	22	1.03
2 x 1-1/2	3RN3224T	3RN3224N	62	70	27	38	18	26	1.03

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Reducing Hex Nipples are available in BSPT, NPT configurations - ASME B16.11-2016

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

BSPT threads are to ISO 7.1  
NPT threads are to ANSI B2.1

Larger sizes are available upon request

We also keep Equal Hex Nipples as BSPT and NPT threads in 3000lb 316/L



Hex Nipples can also be supplied as part of our low pressure 150lb range

