



SIZE	G BSPP	CODE	DIMENSIONS							
			A	B	C	D	E	F	A/F	KG EACH
1/4	1/4	FHTC04	45.5	18	4.3	6.3	4.5	4.5	18	0.05
3/8	3/8	FHTC06	51.3	21.7	4.8	9.53	7.2	7.2	25.7	0.07
1/2	1/2	FHTC08	52.8	21.7	7.1	12.7	9.5	9.5	25.7	0.10
3/4	3/4	FHTC12	64.2	25.9	8.4	19.05	15.1	15.1	31.8	0.17
1	1	FHTC16	74.8	28.3	9.4	25.40	20.6	20.6	38.1	0.22
1-1/4	1-1/4	FHTC20	84	30.1	10.7	31.8	27	27	47.2	0.40
1-1/2	1-1/2	FHTC24	92.7	35.6	11.9	38.1	32.5	32.5	56.4	0.48
2	2	FHTC32	111	38	12.9	50.8	44.3	44.3	69.9	0.69

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Female Swivel Hosetails are available threaded BSPP.

They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1  
Made from 316 (CF8M) stainless steel

We also keep extended barrel nipples in stock, weld nipples too.



TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLA AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK