





SIZE	PRODUCT CODE	PRODUCT CODE	DIMENSIONS			KG EACH
	BSPT	NPT	A (MIN)	F (MIN)	H (MIN)	NG EACH
1/8	3HP02T	3HP02N	10	11.11	6	0.01
1/4	3HP04T	3HP04N	11	15.88	6	0.03
3/8	3HP06T	3HP06N	13	17.46	8	0.05
1/2	3HP08T	3HP08N	14	22.23	8	0.07
3/4	3HP12T	3HP12N	16	26.99	10	0.14
1	3HP16T	3HP16N	19	34.93	10	0.25
1-1/4	3HP20T	3HP20N	21	44.45	14	0.43
1-1/2	3HP24T	3HP24N	21	50.80	16	0.57
2	3HP32T	3HP32N	22	63.50	18	1.03
2-1/2	3HP40T	3HP40N	27	76.20	19	1.62
3	3HP48T	3HP48N	28	88.90	21	2.60

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Hexagonal Plugs are available in BSPT and NPT configurations - ASME B16.11-2016

Pressure rating up to 400 BAR (6000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

BSPT threads are to ISO 7.1 NPT threads are to ANSI B2.1

Larger sizes are available upon request

Hex and Square Plugs can also be supplied as part of our low pressure 150lb range





We also keep Plugs with a Square Head in 6000lb 316/L









