



REDUCING BUSH MALE x FEMALE (BSPP) 316

TYPE A TYPE B









SIZE BSPP (MALE)	SIZE BSPP (FEM)	PRODUCT CODE	PRESSURE (BAR)	TYPE	А	В	С	F	G	н	KG EACH
1/4	1/8	RB0402P	350	В	31	12	18	5	19	12	0.038
3/8	1/8	RB0602P	350	Α	23	12	22	-	22	8	0.040
3/8	1/4	RB0604P	350	В	36	12	22	8	22	17	0.070
1/2	1/4	RB0804P	315	Α	24	14	26	-	24	12	0.057
1/2	3/8	RB0806P	315	В	36	14	26	12	27	17	0.092
3/4	1/4	RB1204P	250	Α	26	16	32	-	32	12	0.10
3/4	3/8	RB1206P	250	Α	26	16	32	-	32	12	0.09
3/4	1/2	RB1208P	250	В	41	16	32	16	32	20	0.14
1	1/2	RB1608P	200	Α	29	18	39	-	41	14	0.15
1	3/4	RB1612P	200	В	47	18	39	20	41	22	0.28
1-1/4	3/4	RB2012P	160	Α	32	20	49	-	50	16	0.26
1-1/4	1	RB2016P	160	В	52	20	49	25	50	25	0.46
1-1/2	1	RB2416P	125	Α	36	22	55	-	55	18	0.34
1-1/2	1-1/4	RB2420P	125	В	58	22	55	32	55	27	0.54
2	1-1/4	RB3220P	80	Α	39	25	69	-	70	21	0.57
2	1-1/2	RB3224P	80	Α	39	25	69	-	70	21	0.45

^{**} DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Reducing Bushes are available in BSPP thread form, with TYPE A + TYPE B patterns available

Made from hexagon bar with a flat sealing face on the female end

Pressure rating up to 200 BAR

Can be supplied with 2.2 Certificate if Conformity - upon request

BSPP Male & Female threads are to ISO 228/1

We stock a wide range of Hydraulic Fittings to suit your requirements



We also keep Female x Male versions of this fitting + Bonded Washers in our Hydraulic range







SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM



