



SIZE	CODE BSP	DIMENSIONS		
		A	B	KG EACH
1/8	MB02	25.6	56	0.05
1/4	MB04	31.8	64	0.08
3/8	MB06	38.1	73	0.13
1/2	MB08	44.5	86	0.23
3/4	MB12	57.2	102	0.36
1	MB16	76.2	121	0.64
1-1/4	MB20	88.9	146	1.04
1-1/2	MB24	108	165	1.39
2	MB32	152.4	203	2.29

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Male Bends are available threaded BSPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
NPT threads are to ANSI B2.1
Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method
Note 2 Temperatures indicated are those of the internal fluid
Note 3 Piping loads, stresses And moments are not taken into account

Not the elbow you are looking for? see below for more options

Four different types of 316 stainless steel elbows are shown. The top left is a 90-degree elbow. The top right is a 45-degree elbow. The bottom left is a 180-degree elbow. The bottom right is a 1/2 elbow.