



- Pressure rated at 1000 PSI (WOG) - 1/4" --> 2"
- Sizes available from 1/4" up to 2"
- 1-Piece Reduced Port
- Threaded Ends: BSPP (ISO 228-1) NPT (ANSI B2.1)
- Investment casting
- Blow-out proof stem
- Inspection Testing: API 598, / EN12266
- 1/4 turn lockable handle
- PED97/23/EC (CE0035) Approved

S.NO.	COMPONENT	MATERIAL
1	HANDLE SLEEVE	PVC
2	HANDLE	304
3	LOCKING	304
4	STEM NUT	304
5	SPRING WASHER	304
6	STEM	304/316
7	PACKING RING	304
8	STEM PACKING	PTFE
9	THRUST WASHER	PTFE
10	CAP	CF8/CF8M
11	BODY	CF8/CF8M
12	BALL SEAT	RPTFE
13	BALL	304/316
14	BALL SEAT	PTFE

SIZE	PRODUCT CODE		ØD	L	H	W	S	CV FACTOR	KG EACH	HEX
	BSPP	NPT								
1/4	RBV04	RBV04N	5	39	31	65	17	1.4	0.04	
3/8	RBV06	RBV06N	6.8	44	36	85	21	1.4	0.11	
1/2	RBV08	RBV08N	9.2	56.5	41	95	25	1.4	0.17	
3/4	RBV12	RBV12N	12.5	59	44	95	32	2	0.25	
1	RBV16	RBV16N	15	71	48	111	38	4.1	0.40	
1-1/4	RBV20	RBV20N	20	78	54	111	49	6.1	0.67	
1-1/2	RBV24	RBV24N	25	83	65	135	53	8.1	0.82	
2	RBV32	RBV32N	32	100	72	135	65	9.5	1.30	

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK