



| SIZE | CODE | DIMENSIONS | | KG EACH |
|-------|------|------------|------|---------|
| | | A | B | |
| 1/8 | S02N | 13 | 17 | 0.02 |
| 1/4 | S04N | 19.5 | 27 | 0.04 |
| 3/8 | S06N | 22.3 | 28 | 0.04 |
| 1/2 | S08N | 28 | 36 | 0.09 |
| 3/4 | S12N | 32.8 | 39 | 0.11 |
| 1 | S16N | 40.5 | 43 | 0.20 |
| 1-1/4 | S20N | 49 | 47.5 | 0.29 |
| 1-1/2 | S24N | 56 | 47.5 | 0.34 |
| 2 | S32N | 66.8 | 55 | 0.49 |
| 2-1/2 | S40N | 82 | 65 | 0.74 |
| 3 | S48N | 96 | 75 | 0.98 |
| 4 | S64N | 122 | 83 | 1.24 |

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Full Sockets are available in NPT threads, and made from cast material, making it a cheap economical way of connecting Male threads through a pipeline

These Cast Sockets are suitable for lower pressures, rather than our standard range - With the outside diameter and length less than our standard Sockets

Pressure rating up to 10 BAR (150 PSI)

BSPP Female threads are to ISO 228/1
Made from 316 (CF8M) Stainless Steel castings

We stock a wide range of BSP Fittings to suit your requirements



We also keep a High Pressure versions of this fitting in our 3K and 6K range

